



SAFETY DATA SHEET

Synthetic Manual Synchromesh Transmission Fluid

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification	
Product identifier	
Product name	Synthetic Manual Synchromesh Transmission Fluid
Product number	MTF
Recommended use of the che	
Application	Lubricating oil.
Uses advised against	Avoid the formation of mists.
-	
Details of the supplier of the s Supplier	AMSOIL INC. Bordner, Ladner, Gervais Scotia Plaza, 40 King St W Toronto, ON, Canada M5H 3Y4 T: +1 416-367-6547
Manufacturer	AMSOIL INC. One AMSOIL Center, Superior, WI 54880, USA. T: +1 715-392-7101 compliance@amsoil.com
Emergency telephone number	<u>r</u>
Emergency telephone	CHEMTREC: Within USA and Canada: 1-800-424-9300 Outside the USA and Canada: +1 703-741-5970 (collect calls accepted) 24/7
2. Hazard(s) identification	
Classification of the substance	e or mixture
OSHA/WHMIS Regulatory Status	This Product is Hazardous under the OSHA Hazard Communication Standard and according to the hazard criteria of the Hazardous Product Regulations.
Physical hazards	Not Classified
Health hazards	Eye Irrit. 2A - H319
Environmental hazards	Aquatic Chronic 3 - H412
Label elements	
Pictogram	
Signal word	Warning

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

Hazard statements	H319 Causes serious eye irritation.
	H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P264 Wash contaminated skin thoroughly after handling.
	P273 Avoid release to the environment.
	P280 Wear eye protection.
	P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
	P337+P313 If eye irritation persists: Get medical advice/ attention.
	P501 Dispose of contents/ container in accordance with national regulations.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information o	n ingredients	
Mixtures		
Hydrogenated base oil		40 - 55%
CAS number: 64742-54-7		
Classification		
Asp. Tox. 1 - H304		
Hydrogenated base oil		1 - <2.5%
CAS number: 64742-53-6		
Classification		
Asp. Tox. 1 - H304		
Hydrogenated base oil		1 - <2.5%
CAS number: 64742-47-8		. 10,0
Classification		
Skin Irrit. 2 - H315		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		
Zinc bis(O,O-diisooctyl) bis(dithiophosphate)	1 - <2.5%
CAS number: 28629-66-5		
Classification		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
Aquatic Chronic 2 - H411		
The full text for all hazard sta	tements is displayed in Section 16.	
Composition comments	The exact percentage is withheld as a trade secret in accordance with 29 CFR	1910.1200.

4. First-aid measures

Description of first aid measures

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.	
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.	
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.	
Skin Contact	Rinse with water.	
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.	
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.	
Most important symptoms and effects, both acute and delayed		
General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.	
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.	
Skin contact	Prolonged contact may cause dryness of the skin.	
Eye contact	Irritating to eyes.	
Indication of immediate medic	al attention and special treatment needed	
Notes for the doctor	Treat symptomatically.	
5. Fire-fighting measures		
Extinguishing media		
Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire- extinguishing media suitable for the surrounding fire.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Special hazards arising from t	he substance or mixture	
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Contains Hydrocarbons. The product is immiscible with water and will spread on the water surface.	
Hazardous combustion products	Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO2).	
Advice for firefighters		

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid contact with skin and eyes. Use protective equipment appropriate for surrounding materials.

Environmental precautions

Environmental precautions Harmful to aquatic life with long lasting effects. Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth		
	or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.		
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.		
7. Handling and storage			

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers. Avoid contact with used product.

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.	
Conditions for safe storage, in	cluding any incompatibilities	
Storage precautions	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.	
Storage class	Chemical storage.	
Specific end uses(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.	
8. Exposure Controls/persona	I protection	
Control parameters		
Occupational exposure limits		
Comments	The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.	
Under conditions which may generate mists, the following exposure limits are recommended: Long-term exposure limit (8-hour TWA): 5 mg/m³ Short-term exposure limit (15-minute): 10 mg/m³		
Exposure controls		
Appropriate engineering controls	Provide adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.	
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.	

Other skin and bodyAppropriate footwear and additional protective clothing complying with an approved standard
should be worn if a risk assessment indicates skin contamination is possible.

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Gas and combination filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work. SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work. SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation on health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation on health and safety at work. SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.
Environmental exposure controls	Keep container tightly sealed when not in use.

9. Physical and Chemical Properties

-	
Information on basic physical and chemical properties	
Appearance	Liquid.
Color	Amber.
Odor	Mild hydrocarbon.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	218°C Cleveland open cup. [ASTM D 92]
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.8623
Solubility(ies)	Not known.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	48.3 cSt @ 40°C 9.7 cSt @ 100°C [ASTM D 445]

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

Explosive properties	Not considered to be explosive.
Oxidizing properties	Does not meet the criteria for classification as oxidizing.
Fire point	238°C Cleveland open cup. [ASTM D 92]
Pour point	-46°C [ASTM D 97]
10. Stability and reactivity	
Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	Oxidizing agents. Acids - oxidizing.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
11. Toxicological information	
Information on toxicological ef	fects
Acute toxicity - oral	
Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u> Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - inhalation Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
Skin corrosion/irritation Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation	
Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitization Respiratory sensitization	Based on available data the classification criteria are not met.
Skin sensitization Skin sensitization	May cause skin sensitization or allergic reactions in sensitive individuals.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
Reproductive toxicity Reproductive toxicity - fertility	Based on available data the classification criteria are not met.

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity -	single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxicity -	repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Dryness of mouth and throat. Coughing, chest tightness, feeling of chest pressure. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Congestion of the lungs may occur, producing severe shortness of breath.
Ingestion	May cause sensitization or allergic reactions in sensitive individuals. A single exposure may cause the following adverse effects: Irritation. Nausea, vomiting. Symptoms following overexposure may include the following: Unconsciousness. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin Contact	May cause skin sensitization or allergic reactions in sensitive individuals. A single exposure may cause the following adverse effects: Redness. Irritation.
Eye contact	A single exposure may cause the following adverse effects: Redness. Irritation.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.
Toxicological information on ingredients.	

Hydrogenated base oil

Acute toxicity - oral		
Notes (oral LD₅₀)	LD₅₀ >5000 mg/kg, Oral, Rat REACH dossier information.	
Acute toxicity - dermal		
Notes (dermal LD₅₀)	LD₅₀ >5000 mg/kg, Dermal, Rabbit REACH dossier information.	
Acute toxicity - inhalation		
Notes (inhalation LC₀)	LC₅₀ >5.53 mg/l, Inhalation, Rat REACH dossier information.	
Skin corrosion/irritation		
Animal data	Dose: 0.5ml, 24 hours, Rabbit Erythema/eschar score: No erythema (0). Edema score: No oedema (0). REACH dossier information.	
Serious eye damage/irritation		
Serious eye damage/irritation	Dose: 0.1ml, 72 hours, Rabbit REACH dossier information.	
Skin sensitization		



Synthetic Manual Synchromesh Transmission Fluid

Skin sensitization	Buehler test - Guinea pig: Not sensitizing. REACH dossier information.
Germ cell mutagenicity	
Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information.
Reproductive toxicity	
Reproductive toxicity - fertility	Screening - NOAEL > 1000 mg/kg/day, Oral, Rat P REACH dossier information.
Reproductive toxicity - development	Developmental toxicity: - LOAEL: 125 mg/kg/day, Dermal, Rat REACH dossier information.

12. Ecological Information

Toxicity

Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

Hydrogenated base oil

Acute aquatic toxicity

Acute toxicity - fish	LL₅₀, 96 hours: > 100 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EL₅₀, 48 hours: > 10000 mg/l, Daphnia magna
Acute toxicity - aquatic plants	NOEL, 72 hours: > 100 mg/l, Pseudokirchneriella subcapitata

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Hydrogenated base oil

Biodegradation	Water - Degradation 31: 28 days Inherently biodegradable.
Bioaccumulative potential	
Bio-Accumulative Potential	No data available on bioaccumulation.
Partition coefficient	Not available.
Mobility in soil	
Mobility	No data available.
Other adverse effects	
Other adverse effects	None known.
13. Disposal considerations	
Waste treatment methods	

SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.
14. Transport information	
General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT, TDG).
UN Number	
Not applicable.	
UN proper shipping name	
Not applicable.	
Transport hazard class(es)	
Transport labels No transport warning sign requ	uired.
Packing group	
Not applicable.	
Environmental hazards	
Environmentally Hazardous So No.	ubstance
Special precautions for user	
Not applicable.	
DOT TIH Zone	Not applicable.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
15. Regulatory information	
Regulatory References	OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation (SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.
US Federal Regulations	
SARA Section 302 Extremely	Hazardous Substances Tier II Threshold Planning Quantities

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities None of the ingredients are listed or exempt.



Synthetic Manual Synchromesh Transmission Fluid

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA) None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Zinc bis(O,O-diisooctyl) bis(dithiophosphate) 1.0 %

CAA Accidental Release Prevention None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I) None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-II) None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances None of the ingredients are listed or exempt.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Hydrogenated base oil

Rhode Island "Right To Know" List None of the ingredients are listed or exempt.

Minnesota "Right To Know" List None of the ingredients are listed or exempt.

New Jersey "Right To Know" List None of the ingredients are listed or exempt.

Pennsylvania "Right To Know" List None of the ingredients are listed or exempt.

Inventories

Canada - DSL/NDSL All the ingredients are listed or exempt.

US - TSCA All the ingredients are listed or exempt. SAVE UP TO 25%

Synthetic Manual Synchromesh Transmission Fluid

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information		
Abbreviations and acronyms used in the safety data sheet	C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control Act; LD/LC/EC = Lethal Dose,Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE= Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very Bioaccumulative.	
Classification abbreviations and acronyms	Eye Irrit. = Eye irritation Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic)	
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/	
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.	
Revision comments	This is the first issue.	
Revision date	4/16/2018	
SDS No.	7405	
Hazard statements in full	 H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. 	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.